

# Airesun Concrete Form Release

## Biodegradable Speciality Concrete Form Release

### Description:

Non-toxic, 100% natural, biodegradable, all-purpose form release oil.

Formulated from seed oils to provide users with a petroleum-free and solvent-free product with no sacrifice in performance compared to other form release oil in the marketplace. Airesun Concrete Form Release reduces the release time of concrete form material to a minimum and prevents buildup. Our product also reduces form cleaning time and rustproofing of metal forms. Providing a superior cast when applied on pre-stressed and precast concrete forms, it does not contain any soil contaminants and totally biodegrades in less than 60 days from the soil, sand, clay, or any other backfill aggregate. This product is listed by the [NSF](#) as acceptable for use as a soluble oil (H3).

### Instructions for use:

Clean form surfaces prior to application in accordance with good concrete application practice. Remove all rust, scale, and/or previously used form release agents from the forms in accordance with good concrete practices.

Spraying is the ideal method of application. Use a spray nozzle that produces a flow of 1/10 of one gallon per minute. May also be applied by roller coating or brushing. A thin film should be applied for maximum economy and efficiency.

### Applications:

For concrete formwork of various types such as foundations, stairs, blocks, sewage pipes and pipes, etc. Precast concrete production

### Airesun Concrete Form Release has the following characteristics:

- Easy to use, biodegradable, free of sulfur and aromatics and is nontoxic, requiring no special application or handling practices.
- Contains no petroleum or CFC's and is therefore Ozone-friendly and safer to handle.
- Non-irritating to skin.
- 100% Biodegradability means no damage to the environment from accidental release into soil or water.
- Flash point is over 130°C and is not restricted for transport or storage.
- Non-staining formula.
- Increases life of valuable forms.
- Thin film for uniform and consistent forming while providing quick release.
- Provides clean and easy form removal.
- Prevents rusting of steel forms and equipment and wood forms from absorbing water and rotting.

*This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not therefore be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property right must be observed. The quality of our products is guaranteed under our General Conditions of Sale.*